

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUXULA

Supplier's address: ENOVATEK GmbH, Sillensteder Straße 213, 26441 Jever, DE

Model identifier: LX800132

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	100	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	10 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	100,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,440 0,403	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	80	Survival factor	-	
the lumen maintenance factor	-			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	-	

(a) '-': not applicable;

(b) '-': not applicable;

Light Source Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4365$ $y=0.4046$

Chromaticity Coordinate: $u'=0.4365$ $v'=0.4046$ ($duv=2.86e-04$)

$T_c=3013K$ Dominant WL: $L_d=582.7nm$ Purity=52.5% Centroid WL: 588.0nm

Ratio: R=24.2% G=73.7% B=2.0% Peak WL: $L_p=600.0nm$ HWL: 125.8nm

Render Index: $R_a=80.6$

R1 =78 R2 =88 R3 =97 R4 =79 R5 =79 R6 =86 R7 =82

R8 =56 R9 =-3 R10=74 R11=79 R12=71 R13=80 R14=98 R15=70

Photo Parameters:

Flux: 12544 lm Fe: 28.666 W Efficacy: 124.8 lm/W

Electrical Parameters:

Luminaire: U=230.0V I=0.4570A P=100.5W PF=0.9550

Lamp : U=0V I=0A P=0W PF=0

Instrument Status:


Scan Range: 380.0nm-800.0nm Interval: 5.0nm[0]
REF=20979 (R=3) %=-1.002%

$I_p=32892$ (G=4, D=55)
PMT: 27.3 centigrade [150.0]

Product Type: LX800132
Number: 232
Temperature: 25.3 deg Test
Operator:
Software: V2.00.100

Manufacturer:
Test Department:
Humidity: 65.0%
Test Date: 2024-06-03 14:25:48
Instrument: PMS-80_V1 (SN: 910045)

Model placed on the Union market from 17/01/2025



EPREL registration number: 2069300

<https://eprel.ec.europa.eu/qr/2069300>

Supplier: ENOVATEK GmbH (Importer)

Website: www.enovatek.de

Customer care service:

Name: ENOVATEK GmbH

Website: www.enovatek.de

Email: info@enovatek.de

Phone: +49 4461 / 7464233

Address:

Sillensteder Straße 213
26441 Jever
Germany